



*Автомобильный  
прицеп*



СССР

**МАЗ-5243**

## АВТОМОБИЛЬНЫЙ ПРИЦЕП МА3-5243

Прицеп МА3-5243 — двухосный, с поворотной тележкой и открытой съемной платформой, предназначен для перевозки различных грузов.

Прицеп рассчитан на буксирование автомобилем грузоподъемностью не менее 6 тонн.

### ТЕХНИЧЕСКАЯ ХАРАКТЕРИСТИКА

Грузоподъемность прицепа, кг . . . . .	6800
Вес прицепа без нагрузки, кг . . . . .	3200
Максимальная скорость буксировки прицепа, км/час . . . . .	70
Колея передних и задних колес, мм . . . . .	1950
Наименьшее расстояние от плоскости дороги до низших точек прицепа (под нагрузкой), мм . . . . .	440

Рама прицепа — сварная, из профильного проката.

Подвеска осей — на четырех продольных полуэллиптических рессорах.

Тормоза — колодочные, барабанного типа, на все колеса; привод пневматический от пневмосистемы автомобиля.

Стояночный тормоз — механический, действует на колодки тормозов задней оси.

Платформа — деревянная, с решетчатыми бортами, усиленными металлической окантовкой. Задний и боковые борта откидные.

Внутренние размеры платформы, мм:

длина . . . . .	4940
ширина . . . . .	2322
высота бортов . . . . .	610

Сценное устройство — дышло треугольное, сварное, со съемной тяговой петлей

Габаритные размеры, мм:

длина (без дышла) . . . . .	5145
ширина . . . . .	2500
высота . . . . .	2050

## МА3-5243-TRAILER

МА3-5243-Trailer — two-axle, with a turning bogie and open detachable body. It is intended for transporting of various loads.

The trailer is designed for towing by the truck of payload not less than 6 ton.

### SPECIFICATIONS

Trailer payload, kg . . . . .	6800
Trailer weight, kg . . . . .	3200
Maximum speed of trailer towing, km/hr . . . . .	70
Tread of front and rear wheels, mm . . . . .	1950
Road clearance at full load, mm . . . . .	440

Trailer frame — welded, of profile rolled stock.

Axe suspension — on four longitudinal semi-elliptic springs.

Brakes — shoe, drum type, on all wheels; air drive from air system of the truck.

Parking brake — mechanical, acting on brake shoes of rear axle.

Body — wooden, with rack sides reinforced with metal binding. Tail gate and side boards are drop.

Inside dimensions of body, mm:

length . . . . .	4940
width . . . . .	2322
side board height . . . . .	610

Coupling device — beam triangular, welded, with detachable towing.

Overall dimensions, mm:

length (without beam) . . . . .	5145
height . . . . .	2050
width . . . . .	2500

*Nov 25*

*Nov 25*

• ANHÄNGER

• REMORQUE

TRAILER

# MA3-5243



MADE IN USSR

