

# ЗИЛ-ММЗ-4505

ЗИЛ-ММЗ-4505 will help you on  
the construction site and in the open pit



Excellent performance coupled with high efficiency and reliability enable the use of ЗИЛ-ММЗ-4505 dump trucks in industry, agriculture, civil engineering, as well as for construction of hydraulic projects.

The ЗИЛ-ММЗ-4505 dump truck is easy to operate and repair. A reliable hydraulic dumping gear ensures dumping of the platform body through 50° within 15 s. The dumping gear is controlled from the driver's cab.



## Specifications

Payload, kg .....	6,000
Kerb mass, kg .....	4,905
Kerb mass distribution, kN (kgf):	
front axle .....	22.05 (2,205)
rear axle .....	27 (2,700)
Gross mass distribution, kN (kgf):	
front axle .....	29.3 (2,930)
rear axle .....	82 (8,200)
Speed, km/h, max. ....	90
Engine:	
type .....	V8 four-stroke, carburettor
rated power, SAE, at 3,200 min <sup>-1</sup> kW (hp) .....	107 (146)
torque, SAE at 1,800–2,000 min <sup>-1</sup> N·m (kgf·m), max. ....	392 (40)
Platform body:	
capacity, m <sup>3</sup> .....	3.8
floor area, m <sup>2</sup> .....	6.8
dumping time, s .....	15
lowering time, s .....	15



**AVTOEXPORT**



V/O "AVTOEXPORT",  
8, Marx-Engels,  
Moscow 119902, USSR  
Telephone: 202-85-35  
Telex: 411135