BM·VOLVO DUMPER DR 631



- Articulated steering, 4-wheel drive, built for driving both on and off the road
- 10-ton load capacity
- Big--85° --tip angle

- Rugged axles with differential lock; rear axle incorporates hub reduction
- Roomy, well-insulated cab, tested for impact resistance: truck-type driver's seat
- Big wheels, tight turning circle: neverget-stuck performance

Technical particulars

General	
Tare weight	8 tons
Payload	10 "
Length	7.65 m (300 in.)
Width	2.5 m (98 1/2 in.)
Body-side height	2.2 m (86 1/2 in.)
Max. steering angle	45°
Tip angle	85°
Load capacity, struck vol., with	
tailgate	5.4 cu.m. (7 cu.yo

Load capacity, struck vol., with	
tailgate	5.4 cu.m. (7 cu.yd.)
Engine	
Diesel, type	BM 1113 TR
Rating at 2000 r.p.m.	65 h.p. SAE
Max. torque at 1,400 r.p.m	24.5 kgm (177 ft-lb.)

Hydraulics	
Pump	Vickers 25 V 14 A - 6A 10 L
Working pressure	120 kg/cm ² (1,707 psi)
Capacity at 1,500 r.p.m. (engine)	57 1/min. (12 1/2 lmp.gpm)

Gearbox

10 speeds forward, 2 in reverse	
Speed range forward, gears 1 - 10	2.8-25.8 k.p.h. (1.7-16 m.p.h.)
Speed range in reverse, low/high	
Brakes	

Mechanical, on front section	
Tyres	
Front	18.4 - 34/14
Rear	16.00 - 24/12

Electrical	
System	Bosch 12 V
Battery capacity	152 Ah
C	120 111

barrery capacity	152 Ah
Generator rating	130 W
Starter rating	4 h.p.
Optional equipment	

The manufacturers reserve the right to change specifications without prior notice.



BOLINDER-MUNKTELL

Top-hinged tailgate Heavy duty rock body