

# Peterbilt Model 357 Truck Specifications

## **Specifications Include:**

1. Full Frame C Reinforcement
2. RS440 Suspension
3. Top speed 60 mph
4. High Mount Exhaust Routing
5. AD-4 Air Drier
6. 36" Wire and Air Package EOF
7. 2-Stage Air Cleaner-Cyclo Pak FWA

## **Frame and Equipment**

10-5/8" Steel Rails/Steel Cross Members  
Steel Front Cab Support  
Front Wheel Mud Flaps

## **Front Axle and Equipment**

Eaton EFA18F3 18,000 - 20,000 lbs  
Split Progressive. Springs. 18,000 lbs  
Power. Steering TRW TAS65 w/RH Assist.  
Iron Hubs/Cast Drums/16.5 x 6 CAM Brakes  
Stemco Oil Seals Guardian

## **Rear Axle and Equipment**

Eaton DS461P - 46,000 lbs  
Iron Hubs/Cast Drums/16.5 x 7 CAM Brakes  
MGM 3030 Park Brakes Dual Axles  
STEMCO Oils Seals - Guardian  
RS Susp. 46,000 lbs.  
5.38 Ratio for over the road, max speed 60 MPH  
Steel Susp. Insert Over 77" Overhand  
Control Traction Differential (rear)  
Driver controlled Posi-lock forward axle

## **Cummins Engine and Engine Equipment**

L10 - 280 HP @ 2200 RPM  
L10 Turbo Power Torque Cummins Engine  
L-N 100 AMP Alt.  
Immersion Type Pre-heater - 110-120V  
12V Starter  
4 - 12V Batteries 2500 Cold Cranking AMPS  
Bendix 15.5 CFM Air Comp.

## **Engine and equipment (continued)...**

Jake Brake  
Racor Spin-On Water Filter  
Electronic Governor  
5" Exhaust Vert Resilient Cab Mounted  
Alum Exhaust Standpipe  
Exhaust Guard Aluminum-Minimum  
56" Standpipe  
Hand Throttle Vernier Type

### **Transmission and Clutch**

8 Speed Fuller Transmission RTO 1107LL (double low)  
1710 Driveline  
Spicer 14" Ceramic dampened Clutch Plate  
Manual Adjust Clutch Bearing

### **Air and Trailer Equipment**

Bendix DV2 Moisture Ejector  
Connection End of Frame with 7-Way Socket, Hand Valve  
Spring Bracket Modulator Valve

### **Tires and Wheels**

FF: GY 18 Ply 15R22.5 G186  
RR: GY 16 Ply 11R24.5 G186  
Rear Tire Quantity - 8  
FF: ACCUR S/S 22.5 x 12.25 STL WH  
RR: ACCUR 27406N 24.5 x 8.25 STL WH  
Rear Wheel Quantity - 8

### **Fuel Tanks and Accessories**

26" Alum 100 Gal Fuel Tank  
Tank Toc Under Cab RH Side - 100 Gal  
(1) Grip Strut Step  
Alum. Batt. Box with Non-Slip Step LH Side  
Steel Bumper  
Heavy Duty External Tow Eye through front bumper